

TAC 耐熱ダクト MD-45

標準寸法・物性

呼び径		内径 mm	外径 mm	参考質量 g/m	定尺 m	許容圧力 (常温)		許容減圧力 (常温)		許容曲げ半径 mm
mm	inch					Mpa	kgf/cm ²	kPa	mmHg	
50	2	52.5	56.0	365	2	0.007	0.07	-10.5	-79	170
65	2 1/2	67.0	71.5	460	2	0.007	0.07	-10.0	-75	210
75	3	76.0	80.0	525	2	0.007	0.07	-10.0	-75	240
90	3 1/2	91.5	95.0	570	2	0.007	0.07	-9.0	-68	290
100	4	102.5	106.0	635	2	0.007	0.07	-8.0	-60	320
125	5	127.5	131.0	780	2	0.007	0.07	-7.0	-53	380
150	6	152.5	155.0	930	2	0.007	0.07	-6.5	-49	420
175	7	176.5	180.0	1030	2	0.007	0.07	-6.5	-49	510
200	8	202.0	205.0	1240	2	0.007	0.07	-6.0	-45	570
250	10	253.0	256.0	1570	2	0.007	0.07	-4.5	-34	770
300	12	303.5	306.5	2100	2	0.007	0.07	-4.5	-34	920