

# タイパワーホース WS型

## ●寸法および特性(品番 WS-□)

呼径 (Φ)	内径 (mm)	外径 (mm)	ピッチ (mm)	許容圧力 (20℃) Mpa以下/ [kgf/cm <sup>2</sup> 以下]	減圧変形温度 (-0.1Mpa/ -760mmHg) (℃)	許容曲げ 半 径 (mm以上)	参 考 質 量 (g/m)	定尺 (m)
25	25.4±0.5	34.4	8.0	0.50 [5.1]	70	90	320	50
32	31.8±0.5	42.0	9.0	0.50 [5.1]	70	120	440	
38	38.1±0.5	49.2	9.0	0.50 [5.1]	65	150	600	20・50
50	50.8±1.0	62.8	10.0	0.50 [5.1]	65	200	860	
65	63.5±1.0	78.0	14.3	0.50 [5.1]	60	250	1,230	
75	76.0±1.0	91.4	15.1	0.50 [5.1]	60	350	1,520	
100	101.6±1.5	119.0	16.5	0.50 [5.1]	60	500	2,350	
125	127.0±1.5	152.0	22.0	0.50 [5.1]	55	600	4,405	20・(50)
150	152.4 <sup>+2.0</sup> <sub>-1.5</sub>	182.0	24.0	0.50 [5.1]	55	750	5,800	
200	203.0 <sup>+2.0</sup> <sub>-1.5</sub>	237.0	28.0	0.50 [5.1]	50	1,200	8,700	10・20
250	254.0 <sup>+3.0</sup> <sub>-2.0</sub>	293.0	32.0	0.25 [2.5]	50	1,800	11,800	5
300	304.8 <sup>+3.0</sup> <sub>-2.0</sub>	350.0	34.0	0.25 [2.5]	45	2,100	19,000	