

# タイフレキホース V型FPタイプ

## ●寸法および特性(品番 FP-□)

呼径 (Φ)	内径 (mm)	外径 (mm)	ピッチ (mm)	許容圧力 (20°C) Mpa以下/ [kgf/cm <sup>2</sup> 以下]	許容減圧力 (20°C) Kpa以下/ [mmHg以下]	許容曲げ 半 径 (mm以上)	参 考 量 (g/m)	定尺 (m)
50	50.8±1.0	55.3	20.0	0.018 [0.18]	-17.0 [-130]	60	365	5
65	65.5±1.0	70.5	20.0	0.015 [0.15]	-17.0 [-130]	70	475	
75	75.5±1.0	80.5	20.0	0.013 [0.13]	-15.0 [-115]	80	540	
90	91.0±1.0	96.0	24.0	0.010 [0.10]	-13.0 [-100]	95	565	
100	101.5±1.5	106.0	24.0	0.010 [0.10]	-13.0 [-100]	105	625	
125	126.0±1.5	131.0	24.0	0.010 [0.10]	-13.0 [-100]	125	790	
150	152.0±1.5	157.0	24.0	0.008 [0.08]	-9.0 [-70]	150	980	
(175)	177.0±2.0	182.0	24.0	0.006 [0.06]	-8.0 [-62]	175	1,140	
200	202.0±2.0	207.0	24.0	0.005 [0.05]	-6.0 [-45]	200	1,300	
250	253.5±2.5	258.5	24.0	0.003 [0.03]	-3.0 [-23]	255	1,610	
(275)	278.0±2.5	283.5	24.0	0.003 [0.03]	-3.0 [-23]	280	1,780	
300	304.0±3.0	309.5	24.0	0.002 [0.02]	-3.0 [-23]	305	1,910	

( )は受注生産品です。