

タイフレキホース V型PALタイプ

●寸法および特性(品番 PAL-□)

呼径 (Φ)	内径 (mm)	外径 (mm)	ピッチ (mm)	許容圧力 (20°C) Mpa以下/ [kgf/cm ² 以下]	許容減圧力 (20°C) Kpa以下/ [mmHg以下]	許容曲げ 半 径 (mm以上)	参 考 質 量 (g/m)	定尺 (m)
50	50.8±1.0	54.3	20.0	0.032 [0.33]	-17.0 [-130]	60	360	5
65	65.5±1.0	69.5	20.0	0.029 [0.30]	-17.0 [-130]	70	410	
75	75.5±1.0	79.5	20.0	0.025 [0.25]	-15.0 [-115]	80	480	
90	91.0±1.0	95.0	24.0	0.020 [0.20]	-13.0 [-100]	95	485	
100	101.5±1.5	105.0	24.0	0.020 [0.20]	-13.0 [-100]	105	540	
125	126.0±1.5	130.0	24.0	0.018 [0.18]	-13.0 [-100]	125	660	
150	152.0±1.5	156.0	24.0	0.015 [0.15]	-9.0 [-70]	150	820	
(175)	177.0±2.0	181.0	24.0	0.013 [0.13]	-8.0 [-62]	175	980	
200	202.0±2.0	206.0	24.0	0.010 [0.10]	-6.0 [-45]	200	1,050	
250	253.5±2.5	257.0	24.0	0.008 [0.08]	-3.0 [-23]	255	1,340	
(275)	278.0±2.5	282.0	24.0	0.006 [0.06]	-3.0 [-23]	280	1,530	
300	304.0±3.0	308.0	24.0	0.005 [0.05]	-3.0 [-23]	305	1,670	